

## 说明和应用:

- 1200 HV 的表面硬度(维氏硬度)
- 适合加工不锈钢, 比如V2A, V4A, 耐高温钢, 特种合金, 纤维增强塑料等
- 极其耐磨耐用
- 抗锈表面
- 轻轻拍打即可去除锉屑

## 提示:

瑞士锉纹 00/ 德国锉纹 1  
瑞士锉纹 0 / 德国锉纹 2



stumpfauslaufend

419012 扁锉 锉纹00/1

419022 扁锉 锉纹0/2

锉身长度 mm	419012 (RG 4170)	419022 (RG 4170)	横截面 mm
150	●	●	18×4
200	●	●	22×5



stumpfauslaufend

419112 柱锉 锉纹 00/1 普通

419122 柱锉 锉纹 0/2

锉身长度 mm	419112 (RG 4170)	419122 (RG 4170)	横截面 mm
150	○	●	13×4
200	●	●	15×5



spitzauslaufend

419212 半圆锉 锉纹 0/2

419222 半圆锉 锉纹 2/4

锉身长度 mm	419212 (RG 4170)	419222 (RG 4170)	横截面 mm
150	●	-	16×4,5
200	●	●	21×6



spitzauslaufend

419322 三角锉 锉纹 0/2

锉身长度 mm	419322 (RG 4170)	横截面 mm
200	●	14 x14



spitzauslaufend

419422 方锉 锉纹 0/2

锉身长度 mm	419422 (RG 4170)	横截面 mm
150	●	6



spitzauslaufend

419522 圆锉 锉纹 0/2

锉身长度 mm	419522 (RG 4170)	横截面 mm
200	●	8