

组合钳

PRECITool
PRÄZISIONSWERKZEUGE

规格:

- 淬硬工具钢制, 油淬硬化
- 刃口感应淬火硬化加工
- 适合硬线以及软线

**DIN
ISO
5746**



550000 抛光, 多成分套膜手柄

总长 mm	550000 (RG 5506)
160	●
180	●
200	●

组合钳

KNIPEX

规格:

- 特种工具钢制, 油淬硬化
- 刃口感应淬火硬化加工
- 适合硬线以及软线
- 长刃口适合粗线缆

**DIN
ISO
5746**



550001

550001 抛光, 包塑手柄

550003 抛光, 多成分套膜手柄

550008 镀铬, 多成分套膜手柄



550008

总长 mm	550001 (RG 5575)	550003 (RG 5575)	550008 (RG 5575)
160	●	●	●
180	●	●	●
200	●	●	●

强力组合钳

KNIPEX

规格:

- 特种工具钢制
- 油淬火和回火
- 刃口感应淬火硬化处理
- 长刃口适合粗线缆
- 力加强
- 适合长期高负载操作
- 省力 35%
- 适合大横截面电缆 (Ø bis 25 mm)
- 适用于硬线, 软线和钢琴线

**DIN
ISO
5746**



550080

550080 抛光, 包塑手柄

550085 抛光, 多成分套膜手柄

550087 镀铬, 多成分套膜手柄



550085

总长 mm	550080 (RG 5575)	550085 (RG 5575)	550087 (RG 5575)
180	-	●	-
200	●	●	●
225	●	●	●

强力组合钳

PRECITool
PRÄZISIONSWERKZEUGE

规格:

- 特种钢制
- 感应硬化处理
- 适用于硬化的钢缆



550088 抛光, 多成分套膜手柄

总长 mm	550088 (RG 5506)
200	●

重型钳



规格:

- 特种工具钢制
- 高负载
- 精确加工
- 油硬化

DIN
ISO
9243



551003 黑色涂层, 头部抛光

总长 mm	551003 (RG 5575)
160	●
180	●
210	●
225	●
250	●

丝网剪切钳



规格:

- 特种工具钢制
- 锻造和油淬火, 头部抛光
- 刃口感应淬火 (大约 61 HRC)
- 超薄切割头和长手柄
- 高传动比, 省力

DIN
ISO
9242



551103



551203

551103 黑色涂层, 头部抛光

551203 镀镍

总长 mm	551103 (RG 5575)	551203 (RG 5575)
220	●	-
250	●	●
280	●	-
300	●	●

转塔冲孔钳



规格:

- 钳体采用高强度钢板, 粉末涂层
- 带开口弹簧, 开口限位和锁紧装置
- 6 个冲孔刃 (∅ 2,0/2,5/3,0/3,5/4,0/5,0 mm)
- 冲孔刃可更换



551210 转塔冲孔钳

型号	551210 (RG 5575)	刃数量	总长 mm
9070	●	6	220

水泵钳



规格:

- 络钒电工用钢制
- 落锤锻造和油淬火
- 双面导轨 => 双导向
- 坚固耐用的调整结构
- 9-级弧形卡槽调整
- 30% 更多的夹紧空间
- 夹紧面带硬化齿 (大约 61 HRC)
- 自动夹紧钢管和螺母
- 不会从工件上滑落

DIN
ISO
8976



551303



551305

551303 抛光, 包塑手柄

551305 镀铬, 多成分套膜手柄

总长 mm	551303 (RG 5575)	551305 (RG 5575)	开口宽度 mm	适用钢管 Zoll
180	●	-	30	1 1/4
250	●	●	46	2
300	●	●	60	2 3/4

● = 德国中央仓库库存
○ = 德国工厂仓库供货

55/1113