

砂圈涨紧轮 型号GK



说明:

- 带钢柄的可重复使用砂圈涨紧轮
- GK =通过离心力膨胀并紧固砂带的开槽涨紧轮



455300 砂圈涨紧轮

直径x高度 mm	455300 (RG 4578)	最低转速 min ⁻¹	最高转速 min ⁻¹	直径x高度 mm	455300 (RG 4578)	最低转速 min ⁻¹	最高转速 min ⁻¹
15×30	●	26000	36000	30×30	●	13000	19100
22×20	●	18000	26000	45×30	●	8500	12700

砂圈 刚玉 A



说明:

- 涂合成树脂粘合磨粒的耐撕裂布制成, 具有高耐用性和颗粒黏附性
- 粒度根据型号调整
- 粗 = 粒度 50-80
- 细 = 粒度 150



应用:

- 平整粗磨过的焊缝, 磨平点焊焊点, 磨光铸模等
- 加入磨削油可避免砂带的堵塞并延长使用寿命
- 普遍适用于处理钢, 非铁金属和塑料

455400 粗/中粒度 60/80

455410 细 粒度150

直径x高度 mm	455400 (RG 4578)	455410 (RG 4578)	455400 Korn	455410 Korn	直径x高度 mm	455400 (RG 4578)	455410 (RG 4578)	455400 Korn	455410 Korn
15×30	●	●	80	150	30×30	●	●	60	150
22×20	●	●	60	150	45×30	●	●	60	150

砂圈 锆刚玉



说明:

- 磨料 锆刚玉 Z-Cool
- 冷切割防止堵塞



应用:

- 适用于加工不锈钢 (INOX)- 冷切割防止堵塞

455420 粗, 粒度 50

455480 细, 粒度 150

直径x高度 mm	455420 (RG 4578)	455480 (RG 4578)	455420 Korn	455480 Korn	直径x高度 mm	455420 (RG 4578)	455480 (RG 4578)	455420 Korn	455480 Korn
15×30	●	●	50	150	30×30	●	●	50	150
22×20	●	●	50	150	45×30	●	●	50	150