

## 连接夹头 (转接头)



规格:

- 络钒钢制
- 适合动态的持续性负载
- 用于接插六角扳手插件带 1/4 " 内四方头驱动



### 542500 连接夹头

尺寸 机器端3总长 mm	542500 (RG 5450)	驱动 DIN 3126	驱动 插接 3121
A5,5×50	●	A 5,5	E 6,3 1/4"
A5,5×100	●	A 5,5	E 6,3 1/4"
E6,3×50	●	E 6,3	E 6,3 1/4"
E6,3×100	●	E 6,3	E 6,3 1/4"

## 连接夹头 (转接头)



规格:

- 络钒钢制
- 适合动态的持续性负载
- 用于接插批头 带  
1/4 " 六角驱动 DIN 3126 C 6,3
- 带固定环



### 542600 带固定环

尺寸 机器端 四方头 Zoll	542600 (RG 5450)	总长 mm
1/4"	●	25
3/8"	●	30
1/2"	●	35

## 批头 一字



规格:

- DIN 3126-C 6,3
- 坚硬



### 543005 适合一字螺丝

刀厚×刀宽 mm	543005 (RG 5450)	总长 mm	刀厚×刀宽 mm	543005 (RG 5450)	总长 mm
0,6×4,5	●	25	1,0×5,5	●	25
0,8×5,5	●	25	1,2×6,5	●	25

## 批头长款, 适用一字螺丝



规格:

- 1/4 " 外六角驱动批头
- 标准款, 灰色, 特殊钢化表面
- 坚硬



### 543000 适用一字螺丝, 长款

刀厚×刀宽 mm	543000 (RG 5450)	总长 mm	刀厚×刀宽 mm	543000 (RG 5450)	总长 mm
0,5×3	●	39	1,0×5,5	●	39
0,6×3,5	●	39	1,2×6,5	●	39
0,8×4	●	39	1,2×8	●	39
0,6×4,5	●	39	-	-	-

## 批头 BiTorsion 适用一字螺丝



规格:

- 驱动: 1/4 " -Hex-Plus, 类似DIN 3126-C 6,3, ISO 1173
- 驱动: DIN 5264-C, ISO 2380
- 金刚石涂层



### 543010 BiTorsion 适合一字螺丝

刀厚×刀宽 mm	543010 (RG 5450)	总长 mm
0,8×5,5	○	25
1,0×5,5	○	25
1,2×6,5	○	25

● = 德国中央仓库库存  
○ = 德国工厂仓库供货

## 批头 适合内六角螺丝

Hex-Plus®



- 规格:  
 - 1/4" 外六角驱动批头  
 - 标准款,灰色,特殊钢化表面  
 - 坚硬



### 543200 内六角螺丝

尺寸 mm	543200 (RG 5450)	总长 mm	尺寸 mm	543200 (RG 5450)	总长 mm
2	●	25	5	●	25
2,5	●	25	6	●	25
3	●	25	8	●	25
4	●	25	-	-	-

## 冲击批头 适合内六角螺丝

Hex-Plus®



- 规格:  
 - 冲击批头 DIN 3126-F 6,3  
 - 适合市面上常见的冲击/敲击螺丝  
 - 金刚石涂层减少从螺丝头滑落



### 543205 冲击型Hex-Plus

尺寸 mm	543205 (RG 5450)	总长 mm
4	●	50
5	●	50
6	●	50

## 批头 适合内六角螺丝



- 规格:  
 - 1/4" 外六角驱动批头  
 - 标准款,灰色 特殊钢化表面  
 - 坚硬



### 543250 带球头, 适用内六角螺丝

尺寸 mm	543250 (RG 5450)	总长 mm	尺寸 mm	543250 (RG 5450)	总长 mm
2,5	●	25	5	●	25
3	●	25	6	●	25
4	●	25	-	-	-

## 批头 适用十字螺丝 PH



- 规格:  
 - DIN 3126-C 6,3, ISO 1173  
 - 坚硬  
 - 适合十字螺丝 Phillips-Recess



### 543300 PH

尺寸 × 总长 mm	543300 (RG 5450)	尺寸 × 总长 mm	543300 (RG 5450)
PH0 × 25	●	PH2 × 25	●
PH1 × 25	●	PH2 × 50	●
PH1 × 50	●	PH3 × 25	●

## 批头冲击型适合十字螺丝 PH

IMPAKTOR  
Resonance



- 规格:  
 - 冲击型批头 DIN 3126-F 6,3  
 - 适合市面上常见的冲击/敲击型螺丝  
 - 带金刚石涂层防止从螺丝头滑落  
 - 适合十字螺丝 Phillips-Recess



### 543325 冲击型 PH

尺寸	543325 (RG 5450)	总长 mm
PH2	●	50
PH3	●	50

## 批头 适用十字螺丝 PH



- 规格:  
- DIN 3126-C 6,3  
- 适用十字螺丝 Phillips-Recess



- 型号 BDC: BiTorsion®, 金刚石涂层, 安全固定  
型号 BTH: 超硬, 适合木制品螺丝作业  
型号 BTZ: 坚硬, 适合金属制品螺丝作业



543720



543725

543715 PH 型号 BDC

543720 PH 型号 BTZ

543725 PH 型号 BTH

尺寸	543715 (RG 5451)	543720 (RG 5451)	543725 (RG 5451)	总长 mm
PH1	●	●	●	25
PH2	●	●	●	25
PH3	●	●	●	25

## 批头 适用米字螺丝 PZ



- 规格:  
- DIN 3126-C6,3  
- 坚硬  
- 适合米字螺丝 Pozidriv



543400 PZ

尺寸 × 总长 mm	543400 (RG 5450)	尺寸 × 总长 mm	543400 (RG 5450)
PZ0 × 25	●	PZ2 × 25	●
PZ1 × 25	●	PZ2 × 50	●
PZ1 × 50	●	PZ3 × 25	●

## 批头适用米字螺丝 PZ



- 规格:  
- DIN 3126-C 6,3  
- 适用米字螺丝 Pozidriv



- 型号 BDC: BiTorsion®, 金刚石涂层, 安全固定  
型号 BTH: 超硬, 适合木制品螺丝作业  
型号 BTZ: 坚硬, 适合金属制品螺丝作业



543410



543415



543420

543410 PZ BDC

543415 PZ BTH

543420 PZ BTZ

尺寸	543410 (RG 5450)	543415 (RG 5451)	543420 (RG 5450)	总长 mm
PZ1	●	●	●	25
PZ2	●	●	●	25
PZ3	●	●	●	25

## 冲击型批头 适用米字螺丝 PZ



- 规格:  
- 冲击型批头 DIN 3126-F 6,3  
- 适用市面上常见的冲击/敲击型螺丝  
- 金刚石涂层放在从螺丝头滑落  
- 适用米字螺丝 Pozidriv



543445 冲击型 PZ

尺寸	543445 (RG 5450)	总长 mm
PZ2	●	50
PZ3	●	50

- = 德国中央仓库库存  
○ = 德国工厂仓库供货

54/1097



## 批头适用TORX®-螺丝



规格:  
- DIN 3126-C 6,3  
- 适用内-TORX®-螺丝



型号BDC: 金刚石涂层, 安全固定  
型号BTZ: 坚硬, 适合金属制品的螺丝操作



543510



543515

543510 TORX® 型号 BDC

543515 TORX® 型号 BTZ

尺寸	543510 (RG 5451)	543515 (RG 5451)	总长 mm	尺寸	543510 (RG 5451)	543515 (RG 5451)	总长 mm
TX10	●	●	25	TX25	●	●	25
TX15	●	●	25	TX30	●	●	25
TX20	●	●	25	TX40	●	●	25

## 批头 适用 TORX®-螺丝



规格:  
- DIN 3126-C 6,3  
- 适用内-TORX®-螺丝



543500 TORX®

尺寸	543500 (RG 5451)	总长 mm	尺寸	543500 (RG 5451)	总长 mm
TX5	○	25	TX15	●	25
TX6	●	25	TX20	●	25
TX7	●	25	TX25	●	25
TX8	●	25	TX27	●	25
TX9	●	25	TX30	●	25
TX10	●	25	TX40	●	25

## 冲击型批头 适用TORX®-螺丝



规格:  
- 冲击型批头DIN 3126-F 6,3  
- 适用市面上常见的冲击/敲击型螺丝  
- 金刚石涂层方式从螺丝头滑落



543545 冲击型 TORX®

尺寸	543545 (RG 5450)	总长 mm
TX25	●	50
TX30	●	50
TX40	●	50

## 批头棘轮 适用1/4"-批头



规格:  
- 铬钒钢制  
- 带驱动切换拨杆  
- 可直接操作 1/4 "-批头



543600 适用 1/4 "-批头

型号	543600 (RG 5470)
4294	●