

规格:

- 刀身特种钒钢制, 亚光镀铬
- 通体硬化处理
- 刀头发蓝处理
- 人体工学耐冲击3成分热塑性弹性PP手柄
- 永久的颜色区分系统



530605 螺丝刀套装, 一字 / 十字

套件数	530605 (RG 5378)	内含
6	●	一字: 0,533 0,834 1,035,5 1,236,5 十字: PH1 PH2



530607 螺丝刀套装, 一字 / 米字

套件数	530607 (RG 5378)	内含
6	●	一字: 0,533 0,834 1,035,5 1,236,5 米字: PZ1 PZ2



530610 螺丝刀套装, TORX®

套件数	530610 (RG 5378)	内含
5	●	TORX®: T10 15 20 25 30



530615 螺丝刀套装 绝缘VDE, 一字 / 十字

套件数	530615 (RG 5378)	内含
5	●	一字: 0,533 0,834 1,035,5 米字: PH1 PH2



规格:

- 刀身络钒钼钢制
- 硬化处理和发蓝处理
- 绝缘材料刀身直接涂层
- Proturm® 3成分手柄带防滑功能
- 参照 IEC 60900:2004制造
- 适用所有带电作业 直到 1000 V AC / 1500 V DC



531900 VDE-一字螺丝刀

刀宽 mm	531900 (RG 5353)	刀厚 mm	刀长 mm	手柄长 mm
2,5	●	0,40	75	86
3,5	●	0,60	100	100
4,5	●	1,00	125	107
5,5	●	1,00	125	119
6,5	●	1,20	150	119
8,0	●	1,20	175	119



531902 VDE-十字螺丝刀 PH

驱动	531902 (RG 5353)	手柄长 mm	刀长 mm
PH0	●	86	60
PH1	●	107	80
PH2	●	119	100
PH3	●	119	150



531904 VDE-米字螺丝刀 PZ

驱动	531904 (RG 5353)	手柄长 mm	刀长 mm
PZ1	●	107	80
PZ2	●	119	100
PZ3	●	119	150



531906 VDE-TORX®-螺丝刀

驱动	531906 (RG 5353)	手柄长 mm	刀长 mm
T8	●	86	60
T9	●	100	60
T10	●	100	60
T15	●	107	80
T20	●	107	80
T25	●	107	80
T30	●	119	100



规格:

- 刀身络钒钼钢制
- 硬化处理和发蓝处理
- 绝缘材料刀身直接涂层
- Proturm® 3成分手柄带防滑功能
- 参照 IEC 60900:2004制造
- 适用所有带电作业 直到 1000 V AC / 1500 V DC
- 螺丝刀套装带测电笔, 6件套



531908 VDE-螺丝刀套装, 一字/十字

套件数	531908 (RG 5353)	内含
6	●	一字: 2,5375 4,03100 5,53125 十字: PH1380 PH23100 测电笔3,0365



规格:

- Lasertip®-刀身特种钢制
- 保证高耐磨性
- 防止从螺丝头滑出
- 人体工学3成分加强型手柄带防滑功能
- 支持带电作业直到 1000 V
- 介电强度高达 10.000 V
- 发蓝处理和绝缘
- 根据EN 60900

*=不带 Lasertip®



531910 VDE-一字电工螺丝刀

刀宽 mm	531910 (RG 5350)	刀厚 mm	刀长 mm	手柄长 mm
2,5*	●	0,40	80	81
3,0*	●	0,50	100	81
3,5	●	0,60	100	81
4,0	●	0,80	100	98
5,5	●	1,00	125	98
6,5	●	1,20	150	105
8,0	●	1,20	175	112
10,0	●	1,60	200	112



531912 VDE-电工十字螺丝刀 PH

驱动	531912 (RG 5350)	手柄长 mm	刀长 mm
PH0*	●	81	80
PH1	●	98	80
PH2	●	105	100
PH3	●	112	150



531914 VDE-电工米字螺丝刀 PZ

驱动	531914 (RG 5350)	手柄长 mm	刀长 mm
PZ0*	●	81	80
PZ1	●	98	80
PZ2	●	105	100
PZ3	●	112	150



531922 VDE-TORX®-电工螺丝刀

驱动	531922 (RG 5350)	手柄长 mm	刀长 mm
TX9	●	81	80
TX10	●	81	80
TX15	●	98	80
TX20	●	98	80
TX25	●	105	100
TX30	●	105	100



531924 VDE-电工六角螺丝刀

驱动开口宽度 mm	531924 (RG 5350)	刀长 mm	手柄长 mm
2,5	●	80	98
3,0	●	80	98
4,0	●	80	98
5,0	●	80	105
6,0	●	100	105
8,0	●	100	112

