

平头凿 用于金属加工



规格:

- 铬钒空气硬化钢锻造
- 凿头硬化处理
- 金色漆

DIN
6453



560100 平头凿

总长 mm	560100 (RG 5678)	刀宽 mm	刀柄截面 mm
100	●	15	14×9
125	●	18	17×11
150	●	18	17×11
175	●	21	20×12
200	●	24	23×13
250	●	25	23×13
300	●	26	23×13

十字凿 用于金属加工



规格:

- 铬钒空气硬化钢锻造
- 凿头硬化处理
- 金色漆
- 逐渐变细的头部

DIN
6451



560200 十字凿

总长 mm	560200 (RG 5678)	刀宽 mm	刀柄截面 mm
125	●	5	17×11
150	●	6	17×11
175	●	7	17×11
200	●	8	20×12
250	●	9	23×13
300	●	9	23×13

一字凿 用于金属和石料加工



规格:

- 铬钒空气硬化钢锻造
- 凿头硬化处理
- 金色漆
- 长和平的刀头

DIN
6451

240/S: 带扁椭圆刀杆
240/P: 带护套

应用:

适合精细切割和嵌缝作业



560500 一字凿

总长 mm	560500 (RG 5678)	刀宽 mm	刀柄截面 mm
240/S	●	26	26×7
240/P	●	26	26×7

一字凿 弯曲



规格:

- 2边刃
- 刀刃 25° 弯曲
- 手部更自由,可专注于操作
- 附加的边刃可分切和切割
- 最佳的切割几何



560505 弯曲, 2边刃

总长 mm	560505 (RG 5678)
240	●

● = 德国中央仓库库存
○ = 德国工厂仓库供货

56/1167

开槽凿 用于金属加工



规格:

- 铬钒空气硬化钢锻造
- 凿头硬化处理
- 金色漆
- 弯曲的刀头和八角形的刀杆

ähnlich
**DIN
6455**



560600 开槽凿

刀宽 mm	560600 (RG 5678)	刀杆-Ø mm	总长 mm
3	●	10	150
4	●	10	150
5	○	10	150

槽铍 用于金属加工



规格:

- 铬钒空气硬化钢锻造
- 凿头硬化处理
- 金色漆
- 八角刀柄和全方位的切削角

应用:

孔于孔之间开槽



560650 槽铍

刀宽 mm	560650 (RG 5678)	刀杆-Ø mm	总长 mm
2	●	10	125
3	●	10	125
4	●	12	150
5	●	12	150

石凿 用于石料加工



规格:

- 铬钒空气硬化钢锻造
- 凿头硬化处理
- 刀头研磨,带八角刀柄
- 金色漆

**DIN
7256
spitz**

**DIN
7254 B
flach**



560700



560750

560700 平头

560750 尖头

总长 mm	560700 (RG 5678)	560750 (RG 5678)	刀宽 (560700) 扁平 mm	刀杆-Ø mm
200	●	●	23	16
250	●	●	23	16
300	●	●	26	18
400	●	●	30	20
500	●	●	30	20

平头凿



规格:

- 铬钒空气硬化钢锻造
- 凿头硬化处理
- 金色漆



560810 平头凿

总长 mm	560810 (RG 5678)	刀宽 mm	刀杆横截面 mm
250	●	50	23×13

通用护手 用于凿子



规格:

- 特种橡胶制
- 保证固定在刀杆上
- 适合如下刀杆尺寸:八角刀杆从16 到20 mm和 椭圆形刀杆从 20312 到 26313



560780 通用护手

适合凿子尺寸 mm	560780 (RG 5678)
16-26	●

电工凿



规格:

- 铬钒空气硬化钢锻造
- 凿头硬化处理
- 金色漆
- 刀头研磨,八角刀杆
- 特细长款



560800 电工凿

总长 mm	560800 (RG 5678)	刀宽 mm	刀杆-Ø mm
200	●	10	8
250	●	10	8
300	●	14	12

起钉撬棍



规格:

- 6角工具钢锻造
- 硬化处理
- 红色粉末涂层



560900 起钉撬棍

总长 mm	560900 (RG 5678)	刀杆-Ø mm
500	●	18
600	●	18
800	●	18

撬棍



规格:

- 特种钢锻造
- 硬化和发蓝处理



560920 撬棍

总长 mm	560920 (RG 5600)	刀杆-Ø mm	重量 kg
1000	●+	30	5.5
1250	●+	30	6.5
1500	●+	30	8

撬杠



规格:

- 特种钢制
- 镀锌
- 长度400 mm

应用:

撬开生锈的零件,松动轴承,螺栓和齿轮



2165-1



2165-2



2165-3

560950 撬杠

型号	560950 (RG 5672)
2165-1	●
2165-2	●
2165-3	●

● = 德国中央仓库库存
○ = 德国工厂仓库供货

56/1169