

说明和应用:

- 柔韧的
- 磨削力极强
- 蓬松的结构
- 不会堵住
- 用来除锈, 除漆或者清除焊缝
- 用来清除厚实的表面污垢和涂层
- 平面使用
- 用在角磨机上, 不带附件
- 内径22mm

供货:

仅以包装单位!



470212 型号S, 细度特粗

直径 mm	470212 (RG 4720)	最大转速 min ⁻¹
115	●	11000

砂布 用于金属加工



说明:

- 用于金属加工的通用产品
- 片状产品230x280mm
- 刚玉砂布
- 胶合树脂结合

470350 = KL371X,普通

470450 = KL385JF,高柔韧

供货:

仅以包装单位!



470350

470450

470350 砂布,普通,(蓝斜纹布)

470450 砂布,柔韧,(蓝斜纹布)

粒度	470350 (RG 4777)	470450 (RG 4777)	粒度	470350 (RG 4777)	470450 (RG 4777)
40	●	●	180	●	●
60	●	●	220	●	●
80	●	●	320	●	●
100	●	●	400	●	●
120	●	●	600	-	●
150	●	●	-	-	-

砂布 用于油漆和油灰



说明:

- 粒度150-400 = PS11C
- 粒度500-2000 = PS11A
- 片状产品230x280mm
- 防水碳化硅砂纸
- 树脂结合并经浸渍

应用:

用于处理颜料, 油漆和油灰, 特别是在汽车维修和喷漆领域

供货:

仅以包装单位!



470550 砂纸,整张尺寸230x280mm

粒度	470550 (RG 4777)	粒度	470550 (RG 4777)
150	●	600	●
220	●	800	●
240	●	1000	●
320	●	1500	●
400	●	2000	●
500	●	-	-