

轮胎撬棍



- 规格:
- 双工字型, 铬钒钢制
- 镀铬



560960 轮胎撬棍

长度 Zoll	560960 (RG 5672)	总长 mm
8	●	199
12	●	303
16	●	396
20	●	500
24	●	598

顶出冲头



- 规格:
- 铬钒空气硬化钢制
- 8角, 硬化处理
- 带敲击头
- 金色漆

DIN
6450



561100 顶出冲头

冲头-Ø mm	561100 (RG 5678)	总长 × 8角刀杆 mm	冲头-Ø mm	561100 (RG 5678)	总长 × 8角刀杆 mm
2	●	150×10	7	●	150×12
2.5	●	150×10	8	●	150×12
3	●	150×10	10	●	150×12
4	●	150×10	12	●	150×12
5	●	150×10	14	●	150×12
6	●	150×10	—	—	—

顶出冲头套装



- 规格:
- 高硬度合金工具钢制(59 HRC)
- 镀铬和粉末涂层
- 坚固耐用, 表面涂层保护
- 6件套套装: Ø 3, 4, 5, 6, 8, 10 mm
- 防碎



6



6 KS



6 M

561110 顶出冲头套装

型号	561110 (RG 5678)	规格
6	●	塑料夹包装
6KS	●	塑料盒包装
6M	●	金属盒包装



6 RC

561110 顶出冲头套装 颜色标记

型号	561110 (RG 5678)	规格
6RC	●	金属盒包装, 颜色包装

56/1170

- = 德国中央仓库库存
○ = 德国工厂仓库供货