


螺丝刀 带双成分加强型手柄



规格:

- 刀身特种钢制
- 确保高耐磨性
- 亚光镀镍, Lasertip®-刀身
- 人体工学 双成分加强型手柄带防滑保护 (除尺寸 12 和 14)
- Lasertip-刀身防止从螺丝头滑出

*=不带 Lasertip®




530310 一字螺丝刀

刀宽 mm	530310 (RG 5350)	刀厚 mm	刀长 mm	手柄长 mm
2,5	●	0,40	75	70
3,0	●	0,50	80	81
3,5	●	0,60	100	81
4,0	●	0,80	100	98
5,5	●	1,00	125	98
6,5	●	1,20	150	105
7,0	●	1,20	150	105
8,0	●	1,20	175	112
10,0	●	1,60	200	112
12,0	●	2,00	250	117



530320 十字螺丝刀

驱动/刀身长 mm	530320 (RG 5350)	手柄长 mm
PH0/60*	●	81
PH1/80	●	98
PH1/200	●	98
PH2/100	●	105
PH2/200	●	105
PH3/150	●	112



530330 十字螺丝刀 PZ

驱动/刀身长 mm	530330 (RG 5350)	手柄长 mm
PZ0/60*	●	81
PZ1/80	●	98
PZ1/200	●	98
PZ2/100	●	105
PZ2/200	●	105
PZ3/150	●	112

螺丝刀套装 双成分加强型手柄



规格:

- 刀身特种钢制, 确保高耐磨性
- 亚光镀镍 Lasertip®-刀身
- 人体工学双成分加强型手柄带防滑保护 (除尺寸 12 和 14)
- Lasertip-Klinge刀身防止从螺丝头滑出



530340 螺丝刀—一字、十字/PH

套件数	530340 (RG 5350)	内含
6	●	一字: 3,0 4,0 5,5 6,5 mm 十字: PH1/80 PH2/100





规格:

- 刀身珪钼钢制
- 硬化处理, 表面高光镀铬
- 带黑色精密刀头
- Proturm®-三成分手柄带悬挂孔
- ISO 8764标准



530539 一字螺丝刀

驱动	530539 (RG 5352)	刀长 mm	手柄长 mm
2,5	●	75	86
3,5	●	100	100
4,5	●	125	107
5,5	●	125	119
6,5	●	150	119
8,0	●	175	119
10,0	●	200	119



530323 十字螺丝刀

驱动	530323 (RG 5352)	刀长 mm	手柄长 mm
PH0	●	60	86
PH1	●	80	107
PH2	●	100	119
PH3	●	150	119



530333 米字螺丝刀

驱动	530333 (RG 5352)	刀长 mm	手柄长 mm
PZ1	●	80	107
PZ2	●	100	119
PZ3	●	150	119

螺丝刀套装 Proturm®



规格:

- 刀身珪钼钢制
- 硬化处理, 表面高光镀铬
- 带黑色精密刀头
- Proturm®-3成分手柄带悬挂孔
- 组合 530539, 530323 和 530333
- 标准: DIN 5265, ISO 2380, ISO 8764



530521 螺丝刀套装 一字/ 十字

530522 螺丝刀套装 一字/ 米字

套件数	530521 (RG 5352)	530522 (RG 5352)	530521 内含	530522 内含
6	●	●	一字: 3,53100 4,53125 5,53125 6,53150 十字: PH1380 PH23100	一字: 3,53100 4,53125 5,53125 6,53150 米字: PZ1380 PZ23100

● = 德国中央仓库库存
○ = 德国工厂仓库供货

规格:

- 六角刀身特种钢制
- 亚光镀镍 Lasertip®-刀身, 防止从螺丝头滑出
- 3成分加强型手柄带防滑保护
- 带扳手辅助功能 (除尺寸3,5 / 4,0 和 PH0)

*=不带 Lasertip®



530352 一字螺丝刀

刀宽 mm	530352 (RG 5350)	刀厚 mm	刀长 mm	手柄长 mm	扳手辅助 开口宽度 mm
3,5	●	0,60	75	81	—
4,0	●	0,80	90	81	—
4,5	●	0,80	90	98	8
5,5	●	1,00	100	98	10
6,5	●	1,20	125	105	10
7,0	●	1,20	125	105	10
9,0	●	1,60	150	112	13
10,0	●	1,60	175	112	13



530354 十字螺丝刀

驱动	530354 (RG 5350)	刀长 mm	手柄长 mm	扳手辅助 开口宽度 mm
PH0*	●	60	81	—
PH1	●	80	98	8,00
PH2	●	100	105	10,00
PH3	●	150	112	13,00

