

冲击型螺丝起子附件 1/2 "四方头驱动

PROJAHN

规格:

- 特种钢制
- 适合高负载
- 表面发蓝处理
- 带横向空和固定环



548700 1/2"

开口宽度 mm	548700 (RG 5471)	总长 mm	开口宽度 mm	548700 (RG 5471)	总长 mm	开口宽度 mm	548700 (RG 5471)	总长 mm
9	○	39	16	●	39	24	●	39
10	●	39	17	●	39	27	●	39
11	○	39	18	●	39	30	●	48
13	●	39	19	●	39	32	●	48
14	●	39	21	●	39	—	—	—
15	●	39	22	●	39	—	—	—

冲击型螺丝起子附件 1/2 "四方头驱动

PROJAHN

规格:

- 特种钢制
- 适合高负载
- 表面发蓝处理
- 带横向孔和固定环



548705 1/2 "，长款

开口宽度 mm	548705 (RG 5471)	总长 mm	开口宽度 mm	548705 (RG 5471)	总长 mm	开口宽度 mm	548705 (RG 5471)	总长 mm
10	●	77	17	●	77	24	●	77
13	●	77	18	●	77	27	●	78
14	●	77	19	●	77	30	●	78
15	●	77	21	●	77	32	●	78
16	●	77	22	●	77	—	—	—

冲击型螺丝起子附件 1/2 "四方头驱动

PROJAHN

规格:

特深冲击型套筒,适合合金轮毂



548708 1/2 "，特深

型号	548708 (RG 5472)	SW mm	型号	548708 (RG 5472)	SW mm
382017	●	17	382021	○	21
382019	●	19	—	—	—

冲击型螺丝起子附件 1/2 "四方头驱动

PROJAHN

规格:

- 特深冲击型套筒,适合合金轮毂
- 150 mm 长



548706 1/2 "，特深

型号	548706 (RG 5472)	SW mm	型号	548706 (RG 5472)	SW mm
382117	●	17	382121	○	21
382119	○	19	—	—	—

加长杆 1/2 "四方头驱动

PROJAHN

规格:

- 特种钢制
- 适合高负载
- 表面发蓝处理
- 带横向孔和固定环



548710 1/2"

型号	548710 (RG 5471)	总长 mm
387075	●	75
387125	●	125

● = 德国中央仓库库存
○ = 德国工厂仓库供货

54/1107

批头/组套

54

万向接头 1/2 "四方头驱动

PROJAHN
Produktions-ge

规格:

- 特种钢制
- 适合高负载
- 表面发蓝处理
- 带横向空和固定环



548712 1/2"

型号	548712 (RG 5471)
381000	●

锁紧销 适合 1/2 "冲击型螺丝起子附件

PROJAHN
Produktions-ge

548714 1/2 "四方头驱动

型号	548714 (RG 5472)	开口宽度 mm
391410	●	10-14
393216	●	16-32

固定环 适合 1/2 "冲击型螺丝起子附件

PROJAHN
Produktions-ge

548716 1/2 "-四方头驱动

型号	548716 (RG 5472)	开口宽度 mm
381410	●	10-14
383216	●	16-32



冲击型螺丝起子转接头

PROJAHN
Produktions-ge

规格:

- 特种钢制
- 适合高负载
- 表面发蓝处理
- 带横向空和固定环
- 转接头 1/2 "内四方转 3/4 " 外四方



548725 转接头 1/2 "转3/4 "

型号	548725 (RG 5472)
381234	●

冲击型螺丝起子附件 1/2 "四方头驱动

PROJAHN
Produktions-ge

规格:

- 特种钢制
- 适合高负载
- 表面发蓝处理
- 带横向空和固定环



548735 1/2 " 适合内六角螺丝

内六角 mm	548735 (RG 5471)	总长 mm	内六角 mm	548735 (RG 5471)	总长 mm
4	●	78	12	●	78
5	●	78	14	●	78
6	●	78	17	●	78
8	●	78	19	●	78
10	●	78	-	-	-

冲击型螺丝起子附件 1/2“四方头驱动

PROJAHN

规格:

- 特种钢制
- 适合高负载
- 表面发蓝处理
- 带横向孔和固定环



548745 1/2“ TORX®-螺丝

内-TORX®	548745 (RG 5471)	总长 mm
TX30	●	78
TX40	●	78
TX45	●	78

内-TORX®	548745 (RG 5471)	总长 mm
TX50	●	78
TX60	●	78
—	—	—

冲击型螺丝起子套筒附件 1/2“四方头驱动

PROJAHN



548750 1/2“ 3080

3081

3082

3086

3861

型号	548750 (RG 5471)	套件 数	内含
3080	●	10	金属盒包装 10 13 14 16 17 18 19 21 22 24
3081	●	3	套筒滑轨包装,长款 17 19 21
3082	●	3	带保护外壳,适用合金轮毂,长款 17 19 21
3086	●	12	冲击型套筒套装 10 11 13 14 17 19 21 22 23 24 mm,加长杆 125 mm, 万向接头
3861	●	9	内六角冲击型套筒套装 4 5 6 8 10 12 14 17 19
3851	●	9	TX-冲击型套筒套装 TX20 25 27 30 40 45 50 55 60

冲击型螺丝起子附件 3/4“四方头驱动

PROJAHN

规格:

- 特种钢制
- 适合高负载
- 表面发蓝处理
- 带横向孔和固定环



549000

549005

549000 加强型螺丝起子附件 3/4“

549005 冲击型螺丝起子附件 3/4“长款

开口宽度 mm	549000 (RG 5471)	549005 (RG 5471)	549000 总长 mm	549005 总长 mm
17	●	—	51	—
19	●	—	51	—
21	○	○	51	89,5
22	●	●	51	89,5
24	●	●	51	89,5
27	●	●	51	89,5

开口宽度 mm	549000 (RG 5471)	549005 (RG 5471)	549000 总长 mm	549005 总长 mm
30	●	●	54	89,5
32	●	●	56	89,5
34	●	—	57	—
36	●	●	57	89,5
41	●	●	57	89,5
46	●	—	65	—

加长杆 3/4“四方头驱动

PROJAHN

规格:

- 特种钢制
- 适合高负载
- 表面发蓝处理
- 带横向孔和固定环



549010 3/4“

型号	549010 (RG 5471)	总长 mm
487100	●	100
487200	●	200

● = 德国中央仓库库存
○ = 德国工厂仓库供货

54/1109

批头/组套

54

万向接头 3/4 "四方头驱动

PROJAHN
Produktions-Gruppe

- 规格:
- 特种钢制
 - 适合高负载
 - 表面发蓝处理
 - 带横向孔和固定环



549012 3/4"

型号	549012 (RG 5471)
481000	●

冲击型螺丝起子转接头

PROJAHN
Produktions-Gruppe

- 规格:
- 特种钢制
 - 适合高负载
 - 表面发蓝处理
 - 带横向孔和固定环
 - 从 3/4 "内四方到 1/2 "外四方 (型号 483412)
 - 从 3/4 "内四方到 1 "外四方 (型号 483410)



483410



483412

549025 转接头 3/4 "转 1/2 " 或者 1 "

型号	549025 (RG 5471)	四方头
483410	●	3/4"×1"
483412	●	3/4"×1/2"

安全销和固定环 适合 3/4 " 加强型螺丝起子附件

PROJAHN
Produktions-Gruppe

549030 适合四方头驱动 3/4 "

型号	549030 (RG 5472)	开口宽度 mm	规格
482619	●	19 - 26	O-固定环
485027	●	27 - 50	O-固定环
492619	●	19 - 26	S-安全销
495027	●	27 - 50	S-安全销



冲击螺丝起子套筒套装 3/4 "

PROJAHN
Produktions-Gruppe

- 规格:
- 特种钢制
 - 适合高负载
 - 表面发蓝处理
 - 带横向孔和固定环
 - 8件套



549050 3/4"

型号	549050 (RG 5472)	内含
3085	●	26 27 29 30 32 35 36 38 mm

冲击螺丝起子附件 1 "四方头驱动

PROJAHN
Produktions-Gruppe

- 规格:
- 特种钢制
 - 适合高负载
 - 表面发蓝处理
 - 带横向孔和固定环



549400 1 ", 长款

开口宽度 mm	549400 (RG 5472)	总长 mm	开口宽度 mm	549400 (RG 5472)	总长 mm
24	●	90	36	●	90
27	●	90	41	●	90
30	●	90	46	●	100
32	●	90	-	-	-

加长杆 1“四方头驱动

PROJAHN

- 规格:
- 特种钢制
 - 适合高负载
 - 表面发蓝处理
 - 带横向孔和固定环



549410 1“

型号	549410 (RG 5471)	总长 mm
587200	○	200

万向接头 1“四方头驱动

PROJAHN

- 规格:
- 特种钢制
 - 适合高负载
 - 表面发蓝处理
 - 带横向孔和固定环



549412 1“

型号	549412 (RG 5471)
581000	○

冲击型螺丝起子转接头 1“四方头驱动

PROJAHN

- 规格:
- 特种钢制
 - 适合高负载
 - 表面发蓝处理
 - 带横向孔和固定环
 - 1“内四方转 3/4”外四方



549425 1“转 3/4”

型号	549425 (RG 5471)	四方头
581034	●	1"×3/4"

安全销和固定环 适合1“加力螺丝起子

PROJAHN

549430 四方头驱动 1“

型号	549430 (RG 5472)	开口宽度 mm	规格
587019	●	19-26	O-固定环
597019	●	19-26	S-安全销



冲击型螺丝起子套筒套装 1“四方头驱动

PROJAHN

- 规格:
- 特种钢制
 - 适合高负载
 - 表面发蓝处理
 - 带横向孔和固定环
 - 8件套



549450 1“

型号	549450 (RG 5471)	内含
3088	○	金属盒包装,长款: 24 27 30 32 33 34 36 38 mm

● = 德国中央仓库库存
○ = 德国工厂仓库供货

54/1111

批头/组套

54