

螺丝刀 带加强型手柄 (车间螺丝刀)



规格:

- 六角刀身络钒钢制
- 亚光镀镍, 黑色刀头
- 3成分加强型手柄带防滑保护
- 刀宽 4,5 mm以上带扳手辅助功能
- 带敲打帽



530520:

- 尺寸 12,0和14,0 单成分手柄 Weralit II
- 驱动: DIN 5264-A/ISO 2380



530523:

- 尺寸PH4 单成分手柄Weralit II
- 驱动: DIN 5260 PH / ISO 8764 PH

530520 十字螺丝刀带敲打帽

刀宽 mm	530520 (RG 5350)	刀宽 mm	刀长 mm	手柄长 mm	扳手辅助开口宽度 mm
3,5	●	0,60	80	81	—
4,5	●	0,80	90	98	8
5,5	●	1,00	100	105	10
7,0	●	1,20	125	105	10
9,0	●	1,60	150	112	13
10,0	●	1,60	175	112	13
12,0	●	2,00	200	117	16
14,0	●	2,50	250	117	16



530523 十字螺丝刀 带敲打帽

驱动	530523 (RG 5350)	刀长 mm	手柄长 mm	扳手辅助开口宽度 mm
PH1	●	80	98	8
PH2	●	100	105	10
PH3	●	150	112	13
PH4	●	200	117	16

螺丝刀套装 带加强型手柄



规格:

- 六角刀身络钒钢制
- 亚光镀镍, 黑色刀头
- 3成分加强型手柄带防滑保护
- 刀宽 4,5 mm以上带扳手辅助功能
- 带敲打帽



型号 6: 螺丝刀套装组成: 一字和米字螺丝刀, 530520+530523.

型号 6I: 螺丝刀套装敲打帽带内六角接口

包装:

支架透明窗盒装



530526 螺丝刀套装, 一字 / 十字, 带敲打帽

型号	530526 (RG 5350)	内含	型号	530526 (RG 5350)	内含
6	●	一字: 3,5 4,5 5,5 7,0 mm 十字: PH1 PH2	6I	●	一字: 3,5 4,5 5,5 7,0 mm 十字: PH1 PH2

● = 德国中央仓库库存
○ = 德国工厂仓库供货

螺丝刀 不锈钢



规格:

- 刀身不锈钢制
- 高耐腐蚀性能和防锈性能
- 带 Lasertip®-刀身
- 多成分加强型手柄带防滑保护

*=不带Lasertip®



530536 一字螺丝刀

刀宽 mm	530536 (RG 5350)	六角开口宽度 mm
3,0*	●	80×81
3,5	●	100×81
4,0	●	100×98
5,5	●	125×98



530537 十字螺丝刀

刀宽 mm	530537 (RG 5350)	六角开口宽度 mm
PH0*	●	60×81
PH1	●	80×98
PH2	●	100×105
PH3	●	150×112



530538 米字螺丝刀

刀宽 mm	530538 (RG 5350)	六角开口宽度 mm
PZ0*	●	60×81
PZ1	●	80×98
PZ2	●	100×105
PZ3	●	150×112

螺丝刀套装 不锈钢



规格:

- 刀身不锈钢制
- 高耐腐蚀性能和防锈性能
- 带 Lasertip®刀身
- 多成分加强型手柄带防滑保护
- 6件套, 支架透明窗盒装



530540 螺丝刀套装, 一字和十字

套件数	530540 (RG 5350)	内含
6	●	一字: 3,0380 4,03100 5,53125 6,53150 十字: PH1380 PH23100



530542 螺丝刀-一字, 十字, PH和PZ

套件数	530542 (RG 5350)	内含
6	●	一字: 3,0380 6,53150 十字: PH1380 PH23100 米字: PZ1380 PZ2310



专家螺丝刀



规格和应用:

- 刀身不锈钢制, 防锈
- 加强型手柄带防滑保护和固定夹子
- 适用轻松的螺丝操作和一般作业比如 胎面花纹深度的测量, 测试生锈或去除污垢。



530254 一字螺丝刀

型号	530254 (RG 5350)	刀长 mm	手柄长 mm
MS	●	50	70

螺丝刀 短款



规格:

- 刀身络钒钢制
- 镀铬和硬化处理
- 特别适合狭小空间作业

530240+530250: 黑色刀头

530242+530252: 镀铬 Top®-刀头, SoftFinish®- 多成分手柄防滑保护



530240



530242

530240 WERA-螺丝刀, 一字

刀宽 mm	530240 (RG 5350)	刀厚 mm	刀长 mm
3,5	●	0,60	25
4,0	●	0,80	25
5,5	●	1,00	25
6,5	●	1,20	25
8,0	●	1,20	25

530242 WIHA-螺丝刀, 一字

刀宽 mm	530242 (RG 5353)	刀厚 mm	刀长 mm
4,0	●	0,80	25
5,5	●	1,00	25
6,5	●	1,20	25



530250



530252

530250 WERA-短十字螺丝刀

驱动	530250 (RG 5350)	刀长 mm
PH01	●	25
PH02	●	25
PZ01	●	25
PZ02	●	25

530252 WIHA-短十字螺丝刀

驱动	530252 (RG 5353)	刀长 mm
PH01	●	25
PH02	●	25
PZ01	●	25
PZ02	●	25

螺丝夹爪



规格:

- 适用所有常见的螺丝刀 刀身直径-Ø 4,5到6,0 mm (PH/PZ 1+2)
- 不带磁性也可工作
- 耐磨材料制造
- 拔出力远超EN-Norm
- 带飞轮套
- 自动释放螺丝

应用:

适用狭小空间的螺丝固定。适用于车间和电工操作。



530598 螺丝夹爪

型号	530598 (RG 5350)
1441	●

● = 德国中央仓库库存
○ = 德国工厂仓库供货

53/1077