

	P N/mm <sup>2</sup>	K HB	N N/mm <sup>2</sup>
126422	<1200	<300	塑料
126425	<1200	<300	塑料
vc = m/min.			
126422	120-250	60-250	80-200
126425	120-250	60-250	80-200



技术说明:

- 带内冷孔
- 基材采用带冷却槽的高性能, 耐磨性高的硬质合金
- 可加工材料极其广泛
- 冷却槽有助于深孔加工
- EU齿距可优化孔加工
- 整体硬质合金基材确保刀具刚性, 前提是刀具刃口和刀杆同心度高
- 圆柱形NC刀杆特别适合液压夹头或者高精度筒夹制造

公差:

- 整体和一半直径  $\varnothing =$  公差范围 H7 符合 DIN 1420
- 公制直径至  $-\varnothing 5,50 = +0,004/0$
- 公制直径大于等于  $-\varnothing 5,51 = +0,005/0$



Typ DL (Durchgangsloch)



Typ SL (Sackloch)



Durchgangsloch



Sackloch

126422 BECK, 整体硬质合金, 带IK, TiAlN涂层, DL型

126425 BECK, 整体硬质合金, 带IK, TiAlN涂层, SL型

d <sub>1</sub> (H7) mm	126422 (RG 1271)	126425 (RG 1271)	l <sub>1</sub> mm	l <sub>2</sub> mm	l <sub>3</sub> mm	l <sub>4</sub> mm	d <sub>2</sub> (h6) mm	Z DL/ SL	f mm/U	d <sub>1</sub> (H7) mm	126422 (RG 1271)	126425 (RG 1271)	l <sub>1</sub> mm	l <sub>2</sub> mm	l <sub>3</sub> mm	l <sub>4</sub> mm	d <sub>2</sub> (h6) mm	Z DL/ SL	f mm/U
3,97	○	○	75	12	36	39	6,0	4/4	0,300-0,500	8,02	○	○	100	16	36	64	8,0	6/6	0,600-1,400
3,98	○	○	75	12	36	39	6,0	4/4	0,300-0,500	8,03	○	○	100	16	36	64	8,0	6/6	0,600-1,400
3,99	○	○	75	12	36	39	6,0	4/4	0,300-0,500	8,50	○	○	100	20	40	60	10,0	6/6	0,600-1,400
4,00	○	○	75	12	36	39	6,0	4/4	0,300-0,500	9,00	○	○	100	20	40	60	10,0	6/6	0,600-1,400
4,01	○	○	75	12	36	39	6,0	4/4	0,300-0,500	9,50	○	○	120	20	40	80	10,0	6/6	0,600-1,400
4,02	○	○	75	12	36	39	6,0	4/4	0,300-0,500	9,97	○	○	120	20	40	80	10,0	6/6	0,600-1,400
4,03	○	○	75	12	36	39	6,0	4/4	0,300-0,500	9,98	○	○	120	20	40	80	10,0	6/6	0,600-1,400
4,50	○	○	75	12	36	39	6,0	4/4	0,300-0,500	9,99	○	○	120	20	40	80	10,0	6/6	0,600-1,400
4,97	○	○	75	12	36	39	6,0	4/4	0,300-0,500	10,00	○	○	120	20	40	80	10,0	6/6	0,600-1,400
4,98	○	○	75	12	36	39	6,0	4/4	0,300-0,500	10,01	○	○	120	20	40	80	10,0	6/6	0,600-1,400
4,99	○	○	75	12	36	39	6,0	4/4	0,300-0,500	10,02	○	○	120	20	40	80	10,0	6/6	0,600-1,400
5,00	○	○	75	12	36	39	6,0	4/4	0,400-1,000	10,03	○	○	120	20	40	80	10,0	6/6	0,600-1,400
5,01	○	○	75	12	36	39	6,0	4/4	0,400-1,000	10,50	○	○	120	20	45	75	12,0	6/6	0,600-1,400
5,02	○	○	75	12	36	39	6,0	4/4	0,400-1,000	11,00	○	○	120	20	45	75	12,0	6/6	0,600-1,400
5,03	○	○	75	12	36	39	6,0	4/4	0,400-1,000	11,50	○	○	120	20	45	75	12,0	6/6	0,600-1,400
5,50	○	○	75	12	36	39	6,0	4/4	0,400-1,000	11,97	○	○	120	20	45	75	12,0	6/6	0,600-1,400
5,97	○	○	75	12	36	39	6,0	4/4	0,400-1,000	11,98	○	○	120	20	45	75	12,0	6/6	0,600-1,400
5,98	○	○	75	12	36	39	6,0	4/4	0,400-1,000	11,99	○	○	120	20	45	75	12,0	6/6	0,600-1,400
5,99	○	○	75	12	36	39	6,0	4/4	0,400-1,000	12,00	○	○	120	20	45	75	12,0	6/6	0,800-2,200
6,00	○	○	75	12	36	39	6,0	4/4	0,400-1,000	12,01	○	○	120	20	45	75	12,0	6/6	0,800-2,200
6,01	○	○	75	12	36	39	6,0	4/4	0,400-1,000	12,02	○	○	120	20	45	75	12,0	6/6	0,800-2,200
6,02	○	○	75	12	36	39	6,0	4/4	0,400-1,000	12,03	○	○	120	20	45	75	12,0	6/6	0,800-2,200
6,03	○	○	75	12	36	39	6,0	6/6	0,400-1,000	13,00	○	○	130	22	45	85	14,0	6/6	0,800-2,200
6,50	○	○	100	16	36	64	8,0	6/6	0,400-1,000	14,00	○	○	130	22	45	85	14,0	6/6	0,800-2,200
7,00	○	○	100	16	36	64	8,0	6/6	0,400-1,000	15,00	○	○	130	22	48	82	16,0	6/6	0,800-2,200
7,50	○	○	100	16	36	64	8,0	6/6	0,400-1,000	16,00	○	○	150	25	48	102	16,0	6/6	0,800-2,200
7,97	○	○	100	16	36	64	8,0	6/6	0,400-1,000	17,00	○	○	150	25	48	102	18,0	8/6	0,800-2,200
7,98	○	○	100	16	36	64	8,0	6/6	0,400-1,000	18,00	○	○	150	25	48	102	18,0	8/6	0,800-2,200
7,99	○	○	100	16	36	64	8,0	6/6	0,400-1,000	19,00	○	○	150	25	50	100	20,0	8/6	0,800-2,200
8,00	○	○	100	16	36	64	8,0	6/6	0,600-1,400	20,00	○	○	150	25	50	100	20,0	8/6	0,800-2,200
8,01	○	○	100	16	36	64	8,0	6/6	0,600-1,400	-	-	-	-	-	-	-	-	-	-

● = 德国中央仓库库存  
○ = 德国工厂仓库供货